LT-1206 parameter list

		1				
Bass speaker:	12 inches 80 Magnetic		TH	D+N 10%		
igh-pitched speaker: 3 inches						
Frequency response:	80HZ~20KHz					
Signal-to-noise ratio S	se ratio S, \geq 80DB Distortion THD: \leq 5%					
Bluetooth Specifications Zhongke AB5312		Bluetooth version:		V5.0		
Transmission range: 10 meters Transmission frequency: 2.46Hz						
Amplifier IC: CS8626				imum output power:	20W	
		Function:				
Bluetooth Interconnection (TWS)		support		music pitch adjust	support	
Bluetooth playback		support		microphone reverb		support
FM radio		support		Microphone volume	adjustment	support
TF card function		support		3.5MM audio input	interface	support
USB input		Support up to 64G		guitar input		not support
music format		Full format support		remote control		support
One key to cancel the original sound		support		Wired microphone i	nput	support
microphone priority		support		Wireless microphone input		support
One-click bass		not support		lantern switch		support
recording		support		lighting effects		lights
Built-in EQ		Support (requires remote control)		External battery input (DC12V)		not support
Loop		Support (requires remote control)		Built-in power strip		not support
battery capacity:	2000mAH	Amplifier built-in battery protection	er built-in battery protection While charging and Support (need to u			/2A charger)
Charging voltage:	voltage: DC 9V			Charging time:	About 4	-6 hours
Standby time: more than	10 hours					
Music time: about 2-3 hours (when playing at 80% volume)				Tripod hole	have	with screws
Pull rod: two sections				wheel:	ABS plastic wheel	
weight:	N4. 15G5. 31				wireless microphone	charger
roduct Size: 350*330*560*890(tie rod height)mm			Accessories:	manual		
Inner packing size: 5-layer color box 395*333*587mm			Foam: Foam			
Package size:				Packing Quantity:		Taiwan/Case